



Verandascreen®

Exceptional sun protection system applicable for every veranda

Verandascreen®

Description

Verandascreen has for many years enjoyed fame as an extremely efficient budgetfriendly outside sun protection screen for both traditional and modern verandas. It is a reliable and beautifully finished sun protecting system. Its discrete design and wide range of colour options in fabrics and profiles make Verandascreen fit perfectly into your home.

Its high-technology screen fabrics ensure comfortable ambient temperatures. Verandascreen filters bright sunlight to achieve a pleasant environment, thus helping prevent discoloration of your interior.

Verandascreen is conveniently and quickly installed by your installation professional and comes with a 5 year warranty.

Product

- Years of experience have made Verandascreen the leader in veranda sun protection systems
- Solid, reliable and beautifully finished sun protection system
- Powered by an electric tubular motor
- Unequalled screen tension thanks to its ingenious stretching system
- All screens have a very high sun protection coefficient
- Soltis polyester fabric available in a very wide range of colours
- Can be combined with Soltis, or acrylic fabrics with a high sun protection coefficient
- Soltis 86/92: no minimal angle of inclination
- Profiles available in all RAL colours

Applications

- Applicable to all horizontal or inclined glazing, such as verandas, glass roofs, skylights, pergolas, conservatories, ...
- New construction and renovation
- Verandascreen is highly suitable for construction projects, which are very demanding in terms of sun protection screens. For best results we recommend consultation between the construction designer, the project developer and the sun protection screen supplier at an early stage.

Technical features

- Max.dimensions:
 - Single screen: Max. width: 4500 mm
Max. prolongation (P): 7000 mm
Maximal surface: 16 m² without support roll
21 m² with support roll
 - Joined screens: Max. width: 9000 mm
Max. prolongation (P): 7000 mm
Maximal surface: 21 m²/part
- Aluminium casing: H 175 x D 230 mm
- Top-bottom mounting

Guarantee

- 10 year color coating warranty
- 5 year product warranty
- In accordance with EN 13561, wind class 3
- Declaration of performance (DOP) 201409-F006



Box



Wind sensor



Joined system

Dealer



RENSON® reserves the right to make technical changes to the products shown. The latest brochures may be downloaded from www.renson.eu

RENSON® Export Department • Tel. +32 (0)56 62 71 11 • export@renson.net

RENSON® Sunprotection-Screens NV
IZ 1 Flanders Field • Kalkhoevestraat 45 • B-8790 Waregem
Tel. +32 (0)56 62 65 00 • Fax +32 (0)56 62 65 09
export@renson.be • www.renson.eu

RENSON® Fabrications LTD
Fairfax Units 1-5 • Birchholt Road • Parkwood Industrial Estate • Maidstone • Kent ME15 9SF
Tel. 01622/754123 • Fax 01622/689478
info@rensonuk.net • www.renson.eu



Creating healthy spaces