




Open side guiding channel




Closed side guiding channel



Open side guiding channel



Closed side guiding channel



Artikelomschrijvingen: zie pagina 2  
Description des articles : voir page 2  
Artikelumschreibungen: siehe Seite 2  
Article descriptions: see page 2

**RENSON**  
Creating healthy spaces

www.renson.eu - 8790 Waregem (Belgium)

This drawing is owned by RENSON and may not be copied or shown to third parties without written permission.

Description :

Side guiding channels

Use. : Fixscreen 100EVO MS1

Part. nr. :

Revision

State :

Creation date : 13/06/2018

Doc. nr.: Exploded view 003

Sheet : 1/1

Scale : 1:4

Drawn : msple

Size :

A3

units in mm

ITEM	PART NUMBER	OMSCHRIJVING	DESCRIPTION	DESCRIPTION	UMSCHREIBUNG
1	P6038630	Zijgeleider vast profiel - open - geponst - 6 m	Coulisse profil fixe - ouvert - perforé - 6 m	Side guiding channel fixed profile - open - punched - 6 m	Seitenführung festes Profil - offen - gestanzt - 6 m
2	P6046710	Ritsgeleider donkergrijs - 6 m	Guide pour fermeture éclair gris foncé - 6 m	Inner rail dark grey - 6 m	Reißverschlussführung dunkelgrau - 6 m
	P6046810	Ritsgeleider lichtgrijs - 6 m	Guide pour fermeture éclair gris clair - 6 m	Inner rail light grey - 6 m	Reißverschlussführung lichtgrau - 6 m
3	P6038730	Zijgeleider afneembaar profiel - geponst - 6 m	Coulisse profil amovible - perforé - 6 m	Side guiding channel removable profile - punched - 6 m	Seitenführung abnehmbares Profil - gestanzt - 6 m
4	G6000494	DIN 912 - M4 x 25 - A2	DIN 912 - M4 x 25 - A2	DIN 912 - M4 x 25 - A2	DIN 912 - M4 x 25 - A2
5	G6020304	Klikker	Clips	Clicker	Klicker
6	G6020302	Afsluitstuk zijgeleider rechts	Pièce de fermeture droite	End plate side guiding channel right	Abschlusselement Seitenführung rechts
	G6020309	Afsluitstuk zijgeleider links	Pièce de fermeture gauche	End plate side guiding channel left	Abschlusselement Seitenführung links
7	P6038830	Zijgeleider vast profiel - gesloten - geponst - 6 m	Coulisse profil fixe - fermée - perforé - 6 m	Side guiding channel fixed profile - closed - punched - 6 m	Seitenführung festes Profil - geschlossen - gestanzt - 6 m