RENSON®
Creating healthy spaces

Sonovent

Fill-in form

Customer | Customer no. | Project | Date

Delivery address

Contact | Tel. | Email

MADE TO MEASURE

GENERAL			TYPE OF SONOVENT							PLACEMENT						FLANGE HEIGHT		COLOR				CONTROL		
Reference	Quantity	Total length* (in mm) flanges included	Model / Size	Airslot (in mm)	Position of the thermal bridge	Glass thickness / Flange thickness	Glazing rubber included	Model nose		Glazed-in position	At transom position	Hidden installation / Covered transom			Naked box	Above	Below	Profiles Mono-color	Profiles Bicolor		End cap and lever	Type	Side	Length control (in mm)
								Standard nose	Flat nose			Toe out	Toe in	V-measure (in mm)		20 mm 25 mm	20 mm 25mm		Inside	Outside	BLack / White	Manually Cord Rod (134 / 144) Motor	Left Right	
			XS S M L XL	10 15 20 25	1 2 3 4 5 6	20 24 28 32 36 40 44	Yes No																	

** Max. 2000 mm (up to 2500 mm for at transom position)*

Additional info (ref. on label, remarks, ...)

Renson® Headquarters • Maalbeekstraat 10 • IZ 2 Vijverdam • B-8790 Waregem • Belgium • Tel. +32 56 30 30 00 • info@renson.eu • www.renson.eu

The customer declares that he/she understands and accepts the general sales conditions.

RENSON®
Creating healthy spaces

Sonovent Compact

Fill-in form

Customer | Customer no. | Project | Date

Delivery address

Contact | Tel. | Email

MADE TO MEASURE

GENERAL			SONOVENT COMPACT 75		SONOVENT COMPACT 65						COLOR				CONTROL			OPTION
Reference	Quantity	Total length* (in mm) flanges included	Glazed-in position	At transom position (by transom profile: ordered separately)	Glazed-in position	At transom position	Covered transom			Naked box (no glass thickness / glass gutter to be specified)	Profiles Monocolor	Profiles Bicolor		End cap and lever	Type	Side	Length control (in mm)	Glazing rubber included
			20 24 28 32 36	20 24 28 32 36	20 24 28 32 36 40 44	20 24 28 32 36 40 44	V74/20	V118/20	V-measure (in mm)			Inside	Outside	Black / White	Manually Cord Rod (134 / 144) Motor	Left Right		Yes No

** Max. 2000 mm (up to 2500 mm for at transom position)*

Additional info (ref. on label, remarks, ...)

Renson® Headquarters • Maalbeekstraat 10 • IZ 2 Vijverdam • B-8790 Waregem • Belgium • Tel. +32 56 30 30 00 • info@renson.eu • www.renson.eu

The customer declares that he/she understands and accepts the general sales conditions.